

• +44 (0) 1208 871185 • sales@neutronfire.com • www.neutronfire.com

• Shire Hall, Quay Street, Lostwithiel, Cornwall. PL22 0BS. United Kingdom

• registered in England and Wales no. 03825226 • vat no. GB 818 0115 58



## **Declaration of Performance: Firebreak Batt**

Number of the declaration of performance: 2024022206 1.

Unique identification code of product type: Firebreak Batt 2.

3. Intended use(es): Firebreak Batt used to reinstate the fire performance of wall and floor constructions where these have been provided with apertures for the penetration of single and multiple service penetrations

Manufacturer: Neutron Fire Technologies Ltd., Shire Hall, Lostwithiel PL22 OBS, U.K.

5. Authorised representative: Not applicable

System(s) of AVCP: System 1

7. European Assessment Document: EAD 350454-00-1104, September 2017

European Technical Assessment: ETA 21/0214

**Technical Assessment Body:** ETA-Danmark A/S Notified Body: 2821, UL International (NL) B.V.

## **Declared performance:**

Basic Work Requirement	Performance(s)
Mechanical resistance and stability	No performance assessed
Safety in case of fire	
Reaction to fire (EN 13501-1)	No performance assessed
Resistance to fire (EN 13501-2)	See ETA 21/0214 – Annex A
Hygiene, Health and the Environment	
Air permeability (EN 1026: 2000)	See ETA 21/0214 – Annex B
Water permeability (EAD 350454-00-1104)	No performance assessed
Release of dangerous substances	Use categories: IA1, S/W3. Declaration of manufacturer
Safety in Use	
Mechanical resistance and stability (EOTA TR001:2003)	No performance assessed
Resistance to impact/movement (EOTA TR001:2003)	No performance assessed
Adhesion	No performance assessed
Protection against noise	
Airborne Sound Insulation (EN10140-2/ EN ISO 717-1)	See ETA 21/0214 – Annex C
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	No performance assessed
Water vapour permeability (EN ISO 12572/ EN 23086)	No performance assessed
General Aspects Relating to Fitness for Use	
Durability and serviceability (EOTA TR 024: 2009)	$Z_1$

Appropriate Technical Documentation and/or Specific Technical Documentation: ETA 21/0214 Link to the online copy of the Declaration of Performance: www.neutronfire.com

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

L. O'Keeffe, Managing Director at Lostwithiel on 22.02.2024

Annex: According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data Sheet according to Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.



## **Declaration of Performance**

According to Annex III of the Regulation (EU) No. 305/2011

 $\epsilon$ 

Neutron Fire Technologies Ltd Shire Hall, Lostwithiel PL22 OBS U.K.

21

2821-CPR-0123

Firebreak Batt - 2024022206

www.neutronfire.com/data

EN 1366-3: 2009 ETA 21/0214 EAD 350454-00-1104

Firebreak Batt is used to reinstate the fire performance of wall and floor constructions where they have been provided with apertures for the penetration of single or multiple services

Single of the	intiple sel vices	
Essential Characteristic	Performance	
Safety in Case of Fire		
Reaction to fire	Class E	
Resistance to fire	See ETA 21/0214 Annex A	
Hygiene, Health and Environment		
Air permeability (EN 1026:2000)	See ETA 21/0214 Annex B	
Release of dangerous substances	Use categories: IA1, S/W3. Declaration	
	of manufacturer	
Safety in Use		
Mechanical resistance and stability	No performance assessed	
Resistance to impact/movement	No performance assessed	
Adhesion	No performance assessed	
Protection against Noise		
Airborne sound insulation	See ETA 21/0214 Annex C	
Energy, Economy and Heat Retention		
Thermal properties	No performance assessed	
Water vapour permeability	No performance assessed	
General aspects relating to fitness for use		
Service and durability	$Z_1$	